

BP

BP系列称重条



坚固耐用的称重条，适合放在任何称量系统底部进行称重，例如：料斗、传送带、辊轮、托盘、料筒等。内含传感器。

## 规格参数

- 配4只IP68不锈钢悬臂梁传感器和2只IP67铝质平行梁传感器,符合OIML R60标准。输入阻值:350 Ohm
- 喷漆钢结构,可抵御由于称重所引起的结构性膨胀或弯曲。抗震能力强。
- 每根称重条配有3m长4芯连接电缆,并配有接线盒。
- 15 Vdc供电。
- IP67接线盒,配5 m长6芯连接电缆,供连接称重显示器使用。
- 可选全不锈钢型号,传感器具有防腐蚀功能。

## 防爆证书

- CCATEX:传感器防爆证书
- JB4QA:防爆接线盒
- DCATEXMECH:称重部分防爆证书,包括称重台 + 接线盒 + 传感器(若连接称重显示器,还需要提供其它相关证书)。




注意

在危险区域内,若直接称重轻金属(例如:铝、镁、钛或其混合材料),需要配不锈钢表面。

## 可选配件

- 标定证书
- CE-M 3000e或3000e+3000e检定证书
- 传感器1区防爆证书:II 1GD ATEX
- 高精度型号

## 产品详情 1



## 可选型号

????

Codice	I x w x h (mm)	Max (kg)	d (g)	<b>M</b> (g)*	<b>M</b> 2R (g)*	d HR (g)*
BPS115 	400x80x105	15	2	5	--	1
BPS130 	400x80x105	30	5	10	5-10	2
BPS160 	400x80x105	60	10	20	--	5
BPS1150 	400x80x105	150	20	50	20-50	10
BPM60	600x105x130	60	10	20	10-20	5
BPM150	600x105x130	150	20	50	20-50	10
BPM300	600x105x130	300	50	100	50-100	20
BPX150	800x135x130	150	20	50	20-50	10
BPX300	800x135x130	300	50	100	50-100	20
BPX600	800x135x130	600	100	200	100-200	50
BPL600	1200x150x120	600	100	200	100-200	50
BPL1500	1200x150x120	1500	200	500	200-500	100
BPL3000	1200x150x120	3000	500	1000	500-1000	200
BPL6000	1200x150x120	6000	1000	2000	1000-2000	500

(\*) 此精度仅在配有相关证书后才有效。



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

**DINI ARGEO  
FRANCE sarl**  
France

**DINI ARGEO  
GMBH**  
Germany

**DINI ARGEO  
UK Ltd**  
United Kingdom

**DINI ARGEO WEIGHING  
INSTRUMENTS Ltd**  
China

**DINI ARGEO  
OCEANIA**  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

**SERVICE ASSISTANCE**

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE