

DFWKXT

"DFWKXT": IP68多功能称重显示器



高性能多功能称重显示器，诸多可用的功能及接口使其适用于广泛的工业和商业领域称重，还可集成于地磅、移动式称重系统等。还提供经CE-M认证型号(OIML R-76 / EN 45501)。

主要特点

- 17个防水功能按键。
- LCD背光显示屏, 可显示6位字高25mm字符, 以及指示当前激活功能的图标。
- 易于清洗的IP68**不锈钢防水**外壳, 可抵御严酷的腐蚀性环境。
- 可在台面、立柱或墙面上使用。
- 尺寸: 264x174x115mm
- 24位4频道 Σ - Δ A/D转换, 速度达200次/秒, 以及8个线性化信号点。
- 10.000e或多量程3x3000e@ 0.3 μ V/e(通过CE-M认证, 用于经贸易结算认证的仪表)。
- 显示分辨率可达800.000, 内部分辨率达3.000.000点。
- 可通过键盘或PC端Dinitool软件进行标定处理或设置参数。
- 内置可充电电池(可维持一个350 Ohm的传感器工作60小时)和110-240Vac电源适配器。
- 至多可连接8个内阻350 Ohm或16个内阻700 Ohm的传感器。

I/O接口

-

产品详情 1



DFWKXT重量指示器附热打印机TPRXT



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.