

JBQ

"JBQ":接线盒



接线盒, 具有角差调整功能, 通过电路板上的可调电阻, 使得秤体达到平衡状态。可以连接2个、3个、4个或10个传感器。连接10个传感器的接线盒内部还装有防漏电及静电干扰的元器件。

性能参数

- 配IP67 ABS保护外盒
- JB10Q型号:配IP68聚酯材质外盒
- 输入电压:24Vdc
- 输入电流:700mA
- 传感器输入信号:1000mV
- 温度影响:50ppm/°C
- JB10Q型号接线盒内部装有防漏电及静电干扰的元器件

尺寸

- JB2Q, JB3Q, JB4Q:120x80x55mm (lxwxh)
- JB10Q:220x120x90mm (lxwxh)





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany

DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 921784

-	
	SALES AND TECHNICAL ASSISTANCE SERVICE