

SPG_C6

SPG系列平行梁传感器, C6精度



用于偏离中心载荷的称重传感器, 适用于使用单个称重传感器制造经 CE-M 认证的衡器; 最大平台尺寸为 600x600 mm。

量程 (kg): 7, 10, 18, 36, 50.

铝合金 IP67 C6精度

规格参数

- C6精度
- 离心负载补偿
- 铝合金结构
- IP67
- 量程可选7 - 50 kg
- 适用于台面尺寸不超过600 x 600 mm的台秤
- 配屏蔽电缆
- 可选OIML及检测证书

性能参数

- 小检定分度值: $V_{min} = E_{Max}/20.000$
- 大检定分度数: $n_{LC} = 6000$
- 灵敏度: $2mV/V \pm 10\%$
- 温度对零点输出的影响: 7kg: $\pm 0,0100\%$ F.S./10K
10kg: $\pm 0,0070\%$ F.S./10K
18kg: $\pm 0,0077\%$ F.S./10K
36kg: $\pm 0,0077\%$ F.S./10K
50kg: $\pm 0,0140\%$ F.S./10K
- 温度对灵敏度的影响:
7kg: $\pm 0,0084\%$ F.S./10K
10kg: $\pm 0,0070\%$ F.S./10K
18kg: $\pm 0,0070\%$ F.S./10K
36kg: $\pm 0,0070\%$ F.S./10K
- 温度补偿范围: $-10^{\circ}C/+40^{\circ}C$
- 工作温度: $-10^{\circ}C/+50^{\circ}C$
- 激励电压: 15 VDC
- 输入阻抗: 300..500 Ohm
- 输出阻抗: 300..500 Ohm
- 零点回复: $0 \pm 0.1\%$ F.S.
- 绝缘阻值: >2000 MOhm
- 安全过载: 150% F.S.
- 极限过载: 300% F.S.
- 6芯屏蔽电缆, 长3m, 直径4.7mm

防爆型号

- 若传感器配有CCATEX防爆证书, 则可以使用在爆炸性环境中, 防爆等级:
ATEX II 1G Ex ia IIC T6 (Ta $-20^{\circ}C/+40^{\circ}C$) TX (Ta $-20^{\circ}C/+65^{\circ}C$) Ga
ATEX II 1D Ex ta IIIC TX $^{\circ}C$ (Ta $-20^{\circ}C/+40^{\circ}C$) TX $^{\circ}C$ (Ta $-20^{\circ}C/+65^{\circ}C$) Da IP65.
此证书包含ATEX CE声明文件 (英文版、德文版、法文版或意大利文版)。
- 注意: 需要为每一只防爆传感器各配一份防爆证书。

产品详情 1



尺寸 (mm)

线缆定义	
颜色	定义
黄	屏蔽
白	输出 +
绿	反馈 +
蓝	输入 +
红	输出 -
灰	反馈 -
黑	输入 -

可选型号

????		
Codice	Piatto Max (mm)	Max (kg)
SPG7C6-1 	300x300	7
SPG10C6-1 	300x300	10
SPG18C6-1 	400x400	18
SPG36C6-1 	450x450	36
SPG50C6-1 	600x600	50



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE