

SPSW

SPSW系列不锈钢平行梁传感器



不锈钢平行梁传感器, 广泛应用于仅安装一只传感器且台面尺寸不超过500x400mm的台秤, 还提供CE-M认证型号。

量程 (kg): 7.5, 15, 30, 50, 100.

17-4 PH不锈钢 IP67 C3精度

规格参数

- C3精度
- 离心负载补偿
- 17-4 PH不锈钢结构
- IP67
- 量程可选7.5 - 100 kg
- 适用于台面尺寸不超过500 x 400 mm的台秤
- 配屏蔽电缆
- 可选OIML及检测证书

性能参数

- 小检定分度值: $V_{min} = E_{Max}/10.000$
- 大检定分度数: $n_{LC} = 3000$
- 灵敏度: $2mV/V \pm 10\%$
- 温度对零点输出的影响: $0.01\% \text{ F.S. } / 10K$
- 温度对灵敏度的影响: $0.001\% \text{ F.S. } / 10K$
- 温度补偿范围: $-10^{\circ}C / +40^{\circ}C$
- 工作温度: $-10^{\circ}C / +50^{\circ}C$
- 蠕变 (30分钟): $0.01\% \text{ F.S.}$
- 激励电压: 15 VDC
- 输入阻抗: $380 \pm 15 \text{ Ohm}$
- 输出阻抗: $359 \pm 5 \text{ Ohm}$
- 绝缘阻值 (100V): $>1000 \text{ MOhm}$
- 安全过载: $300\% \text{ F.S.}$
- 极限过载: $300\% \text{ F.S.}$
- 位移偏量: $<0.5mm$
- 6芯屏蔽电缆, 长3m, 直径5mm

防爆型号

- 若传感器配有CCATEX防爆证书, 则可以使用在爆炸性环境中, 防爆等级:
ATEX II 1G Ex ia IIC T6 (Ta $-20^{\circ}C$ ÷ $+40^{\circ}C$) TX (Ta $-20^{\circ}C$ ÷ $+65^{\circ}C$) Ga
ATEX II 1D Ex ta IIIC TX $^{\circ}C$ (Ta $-20^{\circ}C$ ÷ $+40^{\circ}C$) TX $^{\circ}C$ (Ta $-20^{\circ}C$ ÷ $+65^{\circ}C$) Da IP65
此证书包含ATEX CE声明文件 (英文版、德文版、法文版或意大利文版)。
- 注意: 需要为每一只防爆传感器各配一份防爆证书。

可选型号

????

Codice	Piatto Max (mm)	Max (kg)
SPSW7.5 	500 x 400	7,5
SPSW15 	500 x 400	15
SPSW30 	500 x 400	30
SPSW50 	500 x 400	50
SPSW100 	500 x 400	100
SPSW200 	500 x 400	200



www.diniargeo.com

“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE