

DFWR

"DFWR": 红色明亮的LED显示屏称重显示器



该数字称重显示器具有明亮高效的红色LED显示屏，可从远距离、任何角度观察示数，且光强度可调节。诸多可用的功能及接口使其适用于广泛的工业和商业领域称重。还提供经CE-M认证型号(OIML R-76 / EN 45501)。

主要特点

- 17个防水功能键。
- 6位明亮的字高25mmLED显示屏, 可从远距离、任何角度观察示数, 且光强可调节。
- 可指示当前激活功能的6个LED指示灯。
- IP65防水ABS外壳, 易于清洁, 可在严酷的腐蚀性环境中使用。
- 尺寸: 278x125x186mm
- 可在台面、立柱或墙面上使用。
- 24位A/D 4频道转换器, 转换速度自动选择, 可达200次/秒。多达8个线性化信号点。
- 10.000e或多量程3x3000e @ 0.3 $\mu\text{V/e}$ (通过CE-M认证, 用于经贸易结算认证的仪表)。
- 显示分辨率可达800.000, 内部分辨率达3.000.000点。
- 可通过键盘或PC端Dinitool软件进行标定处理或设置参数。
- 内置可充电电池(可维持一个350 Ohm的传感器工作60小时)和110-240Vac电源适配器。
- 至多可连接8个内阻350 Ohm或16个内阻700 Ohm的传感器。

可选配件

- 附选配盒的数据存储打印机
- 附选配盒的数据存储打印机和热敏打印机
- 附选配盒的控制灯(需配备2个DFIO扩展板)
- 附选配盒的无线电模块
- 实时时钟
- 集成实时时钟功能的Alibi内存板
- USB/RS485/以太网/WI-FI/蓝牙接口
- 2输入+2输出扩展板(至多可连接2块扩展板)
- 16位D/A转换的0-20mA或0-10V模拟输出
- 红外远程遥控器
- 433MHz无线电远程遥控器

功能

- **按键功能:**
清零、去皮、手动去皮、打印和/或传输数据、功能启用、开关机。
17键型号还可: 储存10个皮重、2位数字ID、按键锁及重复打印上一次数据。
- **称重功能:**
 - 重量显示精度x10
 - 净重/毛重或lb/kg转换
 - 重量累计
 - 配方称量
 - +/-误差检重
 - 百分比称量
 - 使用PC/PLC调用保存的重量(需配备Alibi内存板)
 - 计件(分辨率为1500000d)
 - 首次/二次称重
 - 重量锁定与峰值检测
 - 限值控制(需配备DFIO可选配件)





“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
France

DINI ARGEO
GMBH
Germany

DINI ARGEO
UK Ltd
United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
China

DINI ARGEO
OCEANIA
Australia



COMPANY HEADQUARTERS

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 843418

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena • Italy
Tel. +39.0536 921784

SALES AND TECHNICAL ASSISTANCE SERVICE